

Zertifikat *Certificate*

Zertifikatsnummer Certificate No.:

PV 50606014 0003

Berichtsnummer Report No.:

CN23SHR7 003

Genehmigungsinhaber License Holder:

Sany Silicon Energy (Zhuzhou)
Co., Ltd.
Room 518-50, Building 1, Longxin
International, No.255, Tongxia Road,
Tongtangwan Street, Shifeng District
Zhuzhou City,
412005 Hunan
P.R. China

Fertigungsstätte Manufacturing Site:

Sany Silicon Energy (Zhuzhou) Co., Ltd.
Sany Energy Equipment Industrial Park,
No.320 Qingshui Road, Shifeng District,
Zhuzhou City,
412005 Hunan
P.R. China

Prüfzeichen Test Mark:


PID Resistance
Regular
Production
Surveillance

www.tuv.com
ID 1111276485

Geprüft nach Tested according to:

2 PfG 2387/01.18

Geräteidentifikation
Product Identification
Produkt:

PV Module

Product:
Modell:

Modelle sind auf nächste(r) Seite(n) gelistet

Type:
Type designation(s) are listed on the next page(s)
Technische Daten:

Class II acc. to IEC 61140

Technical Data:

For other ratings, refer to the test report.

Gültig bis:

2028-10-12

Date of expiry:
Gültig ab:

2024-04-17

Valid from:
Zertifizierungsstelle:
Certification body:
Ausstellungsdatum:

2024-04-17

Date of issue:

Weichun Li



Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product fulfills above mentioned requirements, the production is subject to surveillance.

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg

<http://www.tuv.com/safety> E-mail: markcheck@tuv.com

Fax: +49 221 806-3935

Zertifikat *Certificate*

Zertifikatsnummer *Certificate No.:*

PV 50606014 0003

Berichtsnummer *Report No.:*

CN23SHR7 003

Produkt *Product:* PV Module

Modell *Type:*

Bezeichnung *Designation:*

Same as Page 0001-0002

In addition:

Max. System Voltage: up to 1500 VDC (Voc at STC):

With ½ cut of mono c-Si cells:

SYMN144R01TBDxxx (xxx=590-620, in steps of 5, 144 cells)

SYMN120R01TBDxxx (xxx=490-520, in steps of 5, 120 cells)

SYMN108R01TBDxxx (xxx=440-470, in steps of 5, 108 cells)

Extension power range for below model types:

Max. system voltage: up to 1500 VDC (Voc at STC):

With ½ cut of mono c-Si cells:

SYMN144TBDxxx (xxx=585, 144 cells)

SYMN120TBDxxx (xxx=480, 485, 120 cells)

SYMN108TBDxxx (xxx=440, 108 cells)

